

PTO/SB/97 (08-00)
Approved for use through 10/31/2002, OMB 0851-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of Information unless it contains a valid CMB control number.

Certificate of Transmission under 37 CFR 1.8

OFFICIAL

I hereby certify that this correspondence is being facsimile transmitted to the Patent and Trademark Office

FAX RECEIVED

on March 12, 2003 to fax no. 703-305-7687.

Date

MAR 1 9 2003

GROUP \$600

ignature

Diane Dunn McKay

Typed or printed name of person signing Certificate

Note: Each paper must have its own certificate of transmission, or this certificate must identify each submitted paper.

Amendment Under Rule 1.116 for Appln. Serial No. 09/675,743 3-Month Extension of Time Notice of Appeal

Burden Hour Statement: This form is estimated to take 0.03 hours to complete. Time will vary depending upon the needs of the Individual case. Any comments on the amount of time required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Examiner: Johnson, V.

#16/amolt B (NE) 4733-1063-20-03

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of Cohen, J. et al.

Serial No. 09/675,743

Filed: September 29, 2000

For: SAFETY HANDLEBAR

Commissioner for Patents

Box: AF

Washington, D.C. 20231

SIR:

Group Art Unit: 3682

FAX RECEIVED

MAR 1 9 2003

GROUP 3600

AMENDMENT UNDER RULE 1.116

In response to the Office Action dated September 17, 2002, please amend the application as follows:

In the Claims:

Please amend claims 1 and 16.

- 1. (Twice Amended) A safety handlebar comprising:
- a frame having opposing, tubular outer ends;
- a shaft having first and second shaft ends, the first shaft end being slidably connected with one of the tubular outer ends;
- a bias member operatively associated with the shaft and the frame so as to bias the second shaft end away from the one tubular end of the frame; and
- a dampener operatively associated with the shaft, the frame and the bias member, said dampener slows a return speed of the bias member upon impact force with said frame towards its pre-impact position to dampen displacement of the second end of the shaft away from the frame,